






**PH16mm 2R1G1B Outdoor led display china,led screen manufacturers**

<b>Model</b>		<b>UNIT-P16-O/F/V/F</b>			
<b>1.LED</b>					
					
Color	Package	Intensity	View Angle	Wavelength	Test Enviro
Red	5mm Oval	550-650mcd	110/50	625nm	25℃,20mA
Green	5mm Oval	1800mcd	110/50	520nm	25℃,20mA
Blue	5mm Oval	350-450mcd	110/50	467nm	25℃,20mA

<b>2.LED Module</b>	
 <b>2R1G1B</b> 	
Resolution	16(H)×8(V)
Pitch	16mm
Density	3906 pixels/m <sup>2</sup> (real density), 15625 pixels/m <sup>2</sup> (virtual density)
LED Arrangement	2R1G1B
Driver Mode	Static Constant Current
Size	256mm×128mm
Mask	Pure Black mask-high contrast screen

<b>3.LED Cabinet</b>
 
Cabinet size can be designed,Special design for easy installation

# SHENZHEN UNIT LED CO., LTD.

Tel: +86-755-29641001, Fax: +86-755-36984024 Website: [www.unit-led.com](http://www.unit-led.com)

Resolution	64 (H)×48(V)
Size	1024 mm×768mm
Modules Quantity	24pcs
Depth	150 mm
Weight	About 48kg

## 4. Electricity Parameter

Optical Ratings	
Brightness	≥7500cd/m <sup>2</sup>
View Angle	110 degree ( horizontal) 70degree(vertical)
Best View Distance	16m-160m
Gray Scale	8bits input, correction with 14bits
Display Color	16.7M
Brightness Adjustment	100 levels
Power Supply	
Operation Power	AC100-240V 50-60HZ Switch-able
Maxim Power Consumption	11.28KW
Average Power Consumption	3.76KW
Control System	
Correction Scale Level	16bits
Frame Update Frequency	60Hz
Screen Refresh Frequency	480Hz
Gamma Correction	-5.0-5.0
Support Input	Composite Video, S-Video, DVI, HDMI., SDI, HD_SDI
Control Distance	Ethernet cable 100m, optical fiber 5km
Support VGA Mode	800×600,1024×768,1280×1024,1600×1200
Color Temperature	5000-9300 adjustable
Brightness Correction	dot by dot, module by module, cabinet by cabinet
Reliability	
Operating Temp.	-20-60 Celsius degree
Operating Humidity	10-95% RH
Operating Life	100,000 hours
MTBF	5000 hours
Continuous Working Time	≥48 hours
Protection Level	IP65
Out of Control Pixel Rate	0.01%

Email: [manager@unit-led.com](mailto:manager@unit-led.com) Msn: [leddisplays@hotmail.com](mailto:leddisplays@hotmail.com)  
Skype: leddisplays Yahoo: [leddisplays@yahoo.cn](mailto:leddisplays@yahoo.cn) Phone: +86-15820768895