




PH18mm 1R1G1B led display manufacturer,led screen project

Model			UNIT-P18-O/T/V/F		
1.LED					
					
Color	Package	Intensity	View Angle	Wavelength	Test Enviro
Red	5mm Oval	550-650mcd	110/50	625nm	25℃,20mA
Green	5mm Oval	1800mcd	110/50	520nm	25℃,20mA
Blue	5mm Oval	350-450mcd	110/50	467nm	25℃,20mA

2.LED Module	
	
Resolution	16(H)×8(V)
Pitch	18mm
Density	3086 pixels/m ² (real density)
LED Arrangement	1R1G1B
Driver Mode	Static Constant Current
Size	288mm×144mm
Mask	Pure Black mask-high contrast screen

3.LED Cabinet

Cabinet size can be designed,Special design for easy installation

SHENZHEN UNIT LED CO., LTD.

Tel: +86-755-29641001, Fax: +86-755-36984024 Website: www.unit-led.com

Resolution	64 (H)×48(V)
Size	1152 mm×864mm
Modules Quantity	24pcs
Depth	150 mm
Weight	About 58 kg

4. Electricity Parameter

Optical Ratings	
Brightness	≥6500cd/m ²
View Angle	110 degree (horizontal) 70 degree(vertical)
Best View Distance	18m-180m
Gray Scale	8bits input, correction with 14bits
Display Color	16.7M
Brightness Adjustment	100 levels
Power Supply	
Operation Power	AC100-240V 50-60HZ Switch-able
Maxim Power Consumption	11.28KW
Average Power Consumption	3.76KW
Control System	
Correction Scale Level	16bits
Frame Update Frequency	60Hz
Screen Refresh Frequency	480Hz
Gamma Correction	-5.0-5.0
Support Input	Composite Video, S-Video, DVI, HDMI., SDI, HD_SDI
Control Distance	Ethernet cable 100m, optical fiber 5km
Support VGA Mode	800×600,1024×768,1280×1024,1600×1200
Color Temperature	5000-9300 adjustable
Brightness Correction	dot by dot, module by module, cabinet by cabinet
Reliability	
Operating Temp.	-20-60 Celsius degree
Operating Humidity	10-95% RH
Operating Life	100,000 hours
MTBF	5000 hours
Continuous Working Time	≥48 hours
Protection Level	IP65
Out of Control Pixel Rate	0.01%

Email: manager@unit-led.com Msn: leddisplays@hotmail.com
Skype: leddisplays Yahoo: leddisplays@yahoo.cn Phone: +86-15820768895