

Ph10mm outdoor led sign, led sign company, led signs

Product model number	UNIT-PH10SORL4-2G16x16
1.Pixel	
Pixel LED	346
Pixel configuration	2G
Wave length (nm)	G: 518 - 520
Pixels pitch (mm)	10
2.Module	
Module size (mm)	160 * 160 * 20
Module resolution(pixel)	16 * 16
3.Unit Cabinet	
Module quantities in a cabinet	4(L) * 3(H)
Unit cabinet size (mm)	640 (L) * 480 (H) * 150
Unit cabinet resolution (pixel)	64 * 48
Unit cabinet material	Iron or Aluminum
Unit cabinet weight(kg)	Aluminum : 16 or Iron : 25
4.Packaging	
Packing way	Four unit cabinets packed into one
Packing box material	Wooden case or Flight box
Packing box size (mm)	1100 * 780 * 480
5.Electricity parameter	
Pixel density (pixels/m ²)	10,000
View angel	Horizontal 110°, Vertical 70°
Best viewing distance(m)	>7
Screen work method	1/4
LED driving method	Constant driving current
Protection grades	IP65
Working temperature(°C)	-20 ~ +60
Humidity(RH)	10 – 95%
Stored temperature (°C)	-30 ~ +70

UNIT SHENZHEN UNIT LED CO., LTD.

Tel: +86-755-29641001, Fax: +86-755-36984024 Website: www.unit-led.com

Screen lifetime(hours)	≥100, 000
Out of controlled dots	≤3/100, 000 (Out of controlled dots means the dots of which the brightness and the wave length are both >10% depart to the normal one)
Maintance way	Back-maintained, modules displaced
Switch power supply	Single Phase AC: 110V/60Hz or 220V/50Hz
Power consumption (w/m ²)	Max: 900, Average: ≥450

Email: manager@unit-led.com Msn: leddisplays@hotmail.com
Skype: leddisplays Yahoo: leddisplays@yahoo.cn Phone: +86-15820768895