

Ph14mm led display sign, led moving sign, led signs

Product model number	UNIT-PH14SORL4-2RG16x8
1.Pixel	
Pixel LED	546
Pixel configuration	2R1G
Wave length (nm)	R: 626-628
Pixels pitch (mm)	14
2.Module	
Module size (mm)	224 * 112 * 20
Module resolution(pixel)	16 * 8
3.Unit cabinet	
Module quantities in a cabinet	4(L) * 6 (H)
Unit cabinet size (mm)	896 (L) * 672 (H) * 180
Unit cabinet resolution(pixel)	64 * 48
Unit cabinet material	Aluminum or Iron
Unit cabinet weight(kg)	Aluminum : 32 or Iron : 42
4.Packaging	
Packing Way	Two unit cabinets packed into one
Packing box material	Wooden case or Flight box
Packing box size (mm)	1020 * 850 * 550
5.electricity parameter	
Pixel density (pixels/m ²)	5106
View angel	Horizontal 110° ; Vertical 70°
Best viewing distance(m)	>8
Communication distance(m)	Internet Wire : 120 Fiber Cable : 1000
Screen work method	1/4
LED driving method	Constant driving current
Software	Support windows series system
Protection grades	IP65

UNIT SHENZHEN UNIT LED CO., LTD.

Tel: +86-755-29641001, Fax: +86-755-36984024 Website: www.unit-led.com

Working temperature(°C)	-20 ~ +60
Humidity(RH)	10 – 95%
Stored temperature (°C)	-30 ~ +70
Screen lifetime(hours)	≥100, 000

Email: manager@unit-led.com Msn: leddisplays@hotmail.com
Skype: leddisplays Yahoo: leddisplays@yahoo.cn Phone: +86-15820768895

UNIT SHENZHEN UNIT LED CO., LTD.

Tel: +86-755-29641001, Fax: +86-755-36984024 Website: www.unit-led.com

Out of controlled dots	≤3/100, 000 (Out of controlled dots means the dots of which the brightness and the wave length are both >10% depart to the normal one)
------------------------	--

 **SHENZHEN UNIT LED CO., LTD.**

Tel: +86-755-29641001, Fax: +86-755-36984024 Website: www.unit-led.com

Maintance way	Back-maintained, modules displaced
Switch power supply	Single Phase AC: 110V/60Hz or 220V/50Hz
Power consumption (w/m ²)	Max: 440, Average: ≥220