

Ph16mm led sign supply, led sign for sale, led signs

Product model number	PH16SORL4-2G16x8
1.Pixel	
Pixel LED	546
Pixel configuration	2G
Wave length (nm)	G: 518-520
Pixels pitch (mm)	16
2.Module	
Module size (mm)	256 * 128 * 20
Module resolution(pixel)	16 * 8
3.Unit cabinet	
Module quantities in a cabinet	4(L) * 6 (H)
Unit cabinet size (mm)	1024 (L) * 768 (H) * 180
Unit cabinet resolution (pixel)	64 * 48
Unit cabinet material	Iron or Aluminum
Unit cabinet weight(kg)	Aluminum : 42 or Iron : 50
4.Packaging	
Packing way	Two unit cabinets packed into one
Packing box material	Wooden case or Flight box
Packing box size (mm)	1150 * 950 * 550
5.Electricity parameter	
Pixel density (pixels/m ²)	3906
View angel	Horizontal 110°, Vertical 70°
Best viewing distance(m)	>11
Screen work method	1/4
LED driving method	Constant driving current
Refresh	≥60

UNIT SHENZHEN UNIT LED CO., LTD.

Tel: +86-755-29641001, Fax: +86-755-36984024 Website: www.unit-led.com

frequency(Hz)	
Protection grades	IP65
Working temperature(°C)	-20 ~ +60
Humidity(RH)	10 – 95%
Stored temperature (°C)	-30 ~ +70
Screen lifetime(hours)	≥100, 000
Out of controlled dots	≤3/100, 000 (Out of controlled dots means the dots of which the brightness and the wave length are both >10% depart to the normal one)
Maintance way	Back-maintained, modules displaced
Switch power supply	Single Phase AC: 110V/60Hz or 220V/50Hz
Power consumption (w/m ²)	Max: 350, Average: ≥200

Email: manager@unit-led.com Msn: leddisplays@hotmail.com
Skype: leddisplays Yahoo: leddisplays@yahoo.cn Phone: +86-15820768895