

## Ph16mm led signs manufacturer, led sign maker, led signs

Product model number	UNIT-PH16SORL4-2R16x8
1.Pixel	
Pixel LED	546
Pixel configuration	2R
Wave length (nm)	R: 626-628
Pixels pitch (mm)	16
2.Module	
Module size (mm)	256 * 128 * 20
Module resolution(pixel)	16 * 8
3.Unit Cabinet	
Module quantities in a cabinet	4 (L) * 6 (H)
Unit cabinet size (mm)	1024(L) * 768(H) * 180
Unit cabinet resolution (pixel)	64 * 48
Unit cabinet material	Aluminum or Iron
Unit cabinet weight(kg)	Aluminum : 42 or Iron : 55
4.Packaging	
Packing way	Two unit cabinets packed into one
Packing box material	Wooden case or Flight box
Packing box size (mm)	1150 * 950 * 550
5.Electricity parameter	
Pixel density (pixels/m <sup>2</sup> )	3906
View angel	Horizontal 110° ; Vertical 70°
Best viewing distance(m)	>6
Communication distance (m)	Internet Wire : 120 Fiber Cable : 1000
Screen work method	1/4

**UNIT SHENZHEN UNIT LED CO., LTD.**Tel: +86-755-29641001, Fax: +86-755-36984024 Website: [www.unit-led.com](http://www.unit-led.com)

LED driving method	Constant driving current
Refresh frequency (Hz)	≥60
Picture display method	Pixels to pixels display synchronized with CRT
Signal interface	DVI
Display format	800 * 600, 1024 * 768, 1280 * 1024
Software	Support windows series system
Protection grades	IP65
Working temperature(°C)	-20 ~ +60
Humidity(RH)	Up to 95
Stored temperature (°C)	-30 ~ +70
Screen lifetime(hours)	≥100, 000
Out of controlled dots	≤3/100,000 (Out of controlled dots means the dots of which the brightness and the wave length are both >10% depart to the normal one)
Maintance way	Back-maintained, modules displaced
Switch power supply	Single Phase AC: 110V/60Hz or 220V/50Hz
Power consumption (w/m <sup>2</sup> )	Max: 220, Average: ≥100

Email: [manager@unit-led.com](mailto:manager@unit-led.com) Msn: [leddisplays@hotmail.com](mailto:leddisplays@hotmail.com)  
Skype: leddisplays Yahoo: [leddisplays@yahoo.cn](mailto:leddisplays@yahoo.cn) Phone: +86-15820768895